


POLYPASS

- Positive ZETA potential
- Steamable
- Sanitizable
- Thermowelded construction
- EC-listed materials for Food contact
- FDA-listed materials per CFR21
- Bio-safety per USP-Plastics (only PH grade)



POLYPASS filter cartridges are manufactured using an innovative media of alumina nanofibers grafted onto borosilicate microfibers in order to have a filter matrix with positive ZETA potential.

Its positive charges greatly interact with the negative contaminant electrical charges contained in the fluid and therefore the media is able to retain particles smaller than its physical passages.

Polypass is used to extend the operating life of expensive membrane filter elements as they reduce colloids, cysts and bio-burden contained in the fluids.

The media has been proven to reduce the concentration of eventual heavy metals present in the water.

The main applications, within the pH range below indicated, are in filtration of aqueous solutions on food & beverages and pharmaceutical industries.

The cartridges are manufactured within a controlled environment.

MATERIALS OF CONSTRUCTION

Filter media	Alumina nanofibers and borosilicate microfibers
Upstream supports	polypropylene
Downstream supports	polypropylene
Internal Core	polypropylene
External Cage	polypropylene
End caps / Adapters	polypropylene

FOOD-SAFETY

POLYPASS filter element materials meet (EU) regulation 10/2011 and its amendments, regulations (EC) 1935/2004 and 1895/2005.

BIO-SAFETY

Filter media and components pass USP Biological Reactivity and Chemical-Physical tests for CLASS VI plastics.


Specific for "PH" grade: the filter meets USP "Water for injection" requirements for particle release and the effluent is Non-Pyrogenic per USP Bacterial Endotoxins (< 0,25 EU/ml).

RECOMMENDED OPERATING CONDITIONS

- max. continuous temperature	65 °C
- max. cumulative time of steam sterilization	20 hours at 125 °C (with cycles of 30 minutes)
- sanitization with hot water	80 °C max
- max. differential pressure	5,0 bar at 25 °C
- recommended change out differential pressure	2,0 bar at 25 °C
- pH range of the fluid	Between 4 and 9

CODE	FILTRATION RATING IN LIQUIDS	MAX WATER FLOW RATE FOR 10" CARTRIDGE
HC	0,5 µm	300 l/h

WATER FLOW RATE FOR 10" CARTRIDGE



POLYPASS ORDERING INFORMATION

PPS - **207** **1** - **HC** - **PH** - -

END FITTING	CODE
DOE: double open end with flat gaskets	200
SOE: open end with (2) O-Ring 2.226 and 2 bayonet locks. Blind end with fin.	207
SOE: open end with (2) O-Ring 2.222. Blind end with fin.	208

FILTRATION RATING micron	CODE
0,5	HC

CODE	PACKING TYPE
No code	Single box
MB	Multiple box

GASKETS	CODE	END FITTING CODE
Silicone	No code	200-207-208
SILICONE	SSS	207-208 With AISI 316 stainless steel ring

CODE	PRODUCT GRADE
GG	General grade; fluxed with water.
PH	Biological grade; prefluxed with non-pyrogenic water; Quality Certification in the box.

CODE	NOMINAL LENGTH
1	10"
2	20"
3	30"
4	40"

Data contained in this bulletin are informative and subject to change without notice. User is responsible for determining whether the product is fit for particular purpose and suitable for user's method of application.



Bea Technologies Spa Via Newton, 4 - 20016 Pero (Milano) ITALY
 Tel +39 02 339271 FAX +39 02 3390713 e-mail: info@bea-italy.com
 web: www.bea-italy.com