
# PharmBiologic Solutions, LLC Advancing custom solutions

1	
(P	R)
	5/

# Absolute Grade Polypropylene Meltblown Cartridge - GATB

- Controlled fiber diameter and density maximizes removal efficiency and ensures consistent performance
- Excellent compatibility with a wide range of chemicals
- Easy cartridge incineration and disposal
- All polypropylene construction
- All end configurations available (glued or thermally-bonded)
- Resists contaminant unloading, even at elevated differential pressures
- Grooved exterior increases surface area

## Flow Rate vs Pressure Drop





#### **Construction Materials**

Filtration Media	Polypropylene
End Caps	Polypropylene
O-Rings/Gaskets	Buna, EPDM, Silicone,
-	Viton <sup>®</sup> , Polyfoam

### Performance Specifications

Micron Ratings: 1, 3, 5, 10, 20, 30, 50, 75, 100 Efficiencies: 1 Micron: 95% 5-100 Micron: 99%

#### **FDA Listed Materials**

Manufactured from materials which are listed for food contact applications in Title 21 of the U.S. Code of Federal Regulations.

## Maximum Recommended

Operating Conditions	
Forward	35 PSID
Reverse	25 PSID
<b>Change Out Differential Pressur</b>	e20 PSID
Temperature	140°F (60°C)

#### **Dimensions (Nominal)**

Length	
-	(24.8 to 102 cm)
Outside Diameter	2.5 inches (6.4 cm)
Inside Diameter	1 inch (2.6 cm)

#### **Purity**

GATB series filter cartridges are free of additives, wetting agents, binders and silicone.

#### **Ordering Information**

GATB	Rating (µ)	А	Length	-	End Cap Style	O-Rings/Gaskets	End Caps
Absolute Grade	1		9.75" (24.76cm)		2 = DOE Flat Gasket	B = Buna	Blank = Glued
	3		9.875″ (25.08 cm)		3 = 222 w/Fin	E = EPDM	TB = Thermally-Bonded
	5		10" (25.4 cm)		4 = 222 w/Flat Cap	S = Silicone	CS = 316ss Compression Spring (TB ONLY)
	10		19.5″ (49.53 cm)		5 = 222 w/Spring	V = Viton®	PC = Polypropylene Core
	20		20″ (50.8 cm)		6 = 226 w/Flat Cap	P = Polyfoam (Gaskets)	
	30		29.25″ (74.29 cm)		7 = 226 w/Fin		
	50		29.5″ (74.93 cm)		8 = 226 w/Spring		
	75		30″ (76.2 cm)		9 = SOE w/ Spring		
	100		39" (99.1 cm)		10 = DOE w/PP Core Extender		
			40″ (101.6 cm)		20 = SOE PP Ext. w/Spring		

DISCLAIMER: Filtration data presented is representative of performance observed in controlled laboratory testing. It is not given as a warranty, specification or statement of fitness for use. Specific performance can vary widely depending on contaminant type, fluid properties, flow rates and environmental conditions. It is recommended that users conduct thorough qualification testing to assure the product functions as required.

